

SAFETY DATA SHEET

1. Identification

Product number	HIL0107855	
Product identifier	Lemon Metered Air Freshener	
Revision date	08-03-2015	
Company information	HILLYARD INC 302 North 4th Street St. Joseph, MO 64501 United States	
Company phone	816-383-8285	
Emergency telephone US	1-800-424-9300	
Version #	03	
Supersedes date	07-14-2015	
Recommended use	Air Freshener	
Recommended restrictions	None known.	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects

 $\wedge \wedge \wedge$

Not classified.

Not classified.

Environmental hazards OSHA defined hazards

Label elements

Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
zard(s) not otherwise ssified (HNOC)	None known.
pplemental information	None.

3. Composition/information on ingredients

Mixtures

_

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 80

Product name: Lemon Metered Air Freshener

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Diethylene Glycol Monoethyl Ether		111-90-0	1 - 2.5
Other components below reportable levels			2.5 - 10

#: This substance has workplace exposure limit(s). *Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	sures
Personal precautions, protective equipment and	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing

protective equipment and emergency procedures	low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
······································	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may

cause spark and become an ignition source. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Value Type Acetone (CAS 67-64-1) PFI 2400 mg/m3 1000 ppm PEL 1800 mg/m3 Propane (CAS 74-98-6) 1000 ppm **US. ACGIH Threshold Limit Values** Components Туре Value Acetone (CAS 67-64-1) STEL 750 ppm TWA 500 ppm Butane (CAS 106-97-8) STEL 1000 ppm **US. NIOSH: Pocket Guide to Chemical Hazards** Components Type Value TWA Acetone (CAS 67-64-1) 590 mg/m3 250 ppm Butane (CAS 106-97-8) TWA 1900 mg/m3 800 ppm Propane (CAS 74-98-6) TWA 1800 mg/m3 1000 ppm US. Workplace Environmental Exposure Level (WEEL) Guides Components Type Value **Diethylene Glycol** TWA 140 mg/m3 Monoethyl Ether (CAS 111-90-0) 25 ppm **Biological limit values ACGIH Biological Exposure Indices** Determinant Specimen Components Value Sampling Time Acetone (CAS 67-64-1) 50 mg/l Urine Acetone * - For sampling details, please see the source document. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates Appropriate engineering should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, controls or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Individual protection measures, such as personal protective equipment If contact is likely, safety glasses with side shields are recommended. Eye/face protection Hand protection For prolonged or repeated skin contact use suitable protective gloves. Skin protection

Product name: Lemon Metered Air Freshener

Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol. Liquefied gas.
Color	Not available.
Odor	Characteristic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.9 % estimated
Flammability limit - upper (%)	9.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	55 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.162 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and tran

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

	Acute toxicity	Narcotic effects.	
AcuteDermai> 7426 mg/kg, 24 HoursLD50Guinea pig> 7426 mg/kg, 24 HoursLD50Rabbit> 7426 mg/kg, 24 HoursLC50Rabbit> 7426 mg/kg, 24 HoursLC50Rat55700 ppn, 3 HoursLC50Rat32 mg/n, 3 HoursLD50Rat32 mg/n, 3 HoursLD50Rat20 mg/kgLD50Rat20 mg/kgLD50Rat32 mg/n, 120 MinutesLC50Rat32 mg/n, 120 MinutesLD50Rat32 mg/n, 120 MinutesLC50Mouse12 mg/n, 120 MinutesLC50Mouse12 mg/n, 120 MinutesLC50Mouse35 mg/nLD50Quinea pig500 mg/kg, DaysLD50Guinea pig474 mg/kg, 24 HoursLD50Guinea pig500 mg/kg, DaysLD50Guinea pig500 mg/kg, DaysLD50Guinea pig474 mg/kg, 24 HoursLD50Guinea pig474 mg/kg, 24 HoursCratT714 mg/kgLD50Guinea pig600 mg/kg, DaysLD50Guinea pig600 mg/kg, DaysGratT714 mg/kgLD50Guinea pig600 mg/kg, DaysLD50Guinea pig600 mg/kg, DaysHU10HU10600 mg/kgHU10HU10	Components	Species	Test Results
Demai- 7426 mg/kg,24 HoursLD50Guinea pig> 9.4 mi/kg,24 HoursRabbit> 7426 mg/kg,24 HoursLC50Rabbit> 9.4 mi/kg,24 HoursLC50Rat5700 ppm, 3 HoursLC50Rat5700 ppm, 3 HoursLD50Rat5800 mg/kgLD50Rat8000 mg/kgLL50Rat5800 mg/kgLL50Rat5800 mg/kgLL50Rat5800 mg/kgLC50Mouse52 % (120 Minutes)LC50Mouse1237 mg/l, 120 MinutesLC50Mouse1237 mg/l, 120 MinutesLC50Mouse52 % (120 Minutes)LC50Guinea pig5900 mg/kg, DaysLD50Guinea pig5900 mg/kg, DaysLD50Guinea pig5900 mg/kg, CaysLD50Guinea pig600 mg/kg, 24 HoursLD50Guinea pig600 mg/kgAuge601 mg/kg601 mg/kgLD50Guinea pig600 mg/kgAuge600 mg/kg600 mg/kgAuge600 mg/kg600 mg/kgAuge600 mg/kg600 mg/kgAuge600 mg/kg600 mg/kg	Acetone (CAS 67-64-1)		
LD50Guinea pig>7426 mg/kg, 24 Hours84bit> 9.4 ml/kg, 24 HoursRabbit> 7426 mg/kg, 24 Hours1000> 7426 mg/kg, 24 Hours1000> 9.4 ml/kg, 24 Hours1000> 55700 ppn, 3 Hours1000> 132 mg/l, 3 Hours1000> 132 mg/l, 3 Hours1000> 8401000> 8401000> 8401000> 8401000> 8401000> 1237 mg/l, 120 Minutes1000> 1246 mg/l, 124 Mours1000> 1246 mg/l, 124 Mours1	Acute		
Partial sector of the sector			
Rabbit > 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours > 9.4 ml/kg, 24 Hours L050 Rat 122 mg/l, 3 Hours 123 mg/l, 3 Hours 123 mg/l, 3 Hours 124 mg/l, 3 Hours 1250 Rat 0ral L050 Rat 201 22 ml/kg 202 22 ml/kg State (CAS 106-97-8) 22 ml/kg Acute 22 ml/kg Inhalation 22 ml/kg L050 Mouse 1237 mg/l, 120 Minutes L050 Mouse 1237 mg/l, 120 Minutes L050 Mouse 1237 mg/l, 120 Minutes Cotal Ext 1355 mg/l L050 Mouse 5900 mg/kg, Days Diethylene Glycol Monoethyl Ether U-Ext 111-90-00 1355 mg/l Ext Rabbit 6500 mg/kg, 24 Hours L050 Guinea pig 5900 mg/kg, 24 Hours L050 Guinea pig 4970 mg/kg, 24 Hours L050 Guinea pig 4970 mg/kg L050 Guinea pig 600 mg/kg L050	LD50	Guinea pig	> 7426 mg/kg, 24 Hours
Inhalation > 9.4 ml/kg, 24 Hours LC50 Rat 55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l Oral 50.1 mg/l LD50 Rat 5800 mg/kg Oral 2.2 ml/kg Sutane (CAS 106-97-8) 2.2 ml/kg Acute 2.2 ml/kg Inhalation 2.2 ml/kg LC50 Mouse 2.37 mg/l, 120 Minutes C50 Mouse 1237 mg/l, 120 Minutes Scote Fat 1355 mg/l Diethytene Glycol Monoethyl Ether (CAS 111-90-0) Rat 3500 mg/kg, Days Ratbit Guinea pig 5900 mg/kg, Days LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours LD50 Guinea pig 6031 mg/kg Mouse 6031 mg/kg 600 mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6000 mg/kg 6000 mg/kg LD50 Guinea pig 6000 mg/kg Mouse 6000 mg/kg 6000 mg/kg Rabbit 6000 mg/kg 6000 mg/kg			> 9.4 ml/kg, 24 Hours
Inhalation LC50 Rat 55700 ppm, 3 Hours 132 mg/l, 3 Hours 132 mg/l, 3 Hours 132 mg/l, 3 Hours 132 mg/l Hours 50.1 mg/l Oral LD50 Rat CAS 106-97-8) Rat CAS 100-97-8) CAS		Rabbit	> 7426 mg/kg, 24 Hours
LC50 Rat 55700 ppm, 3 Hours 132 mg/, 3 Hours 132 mg/, 3 Hours 0ral 50.1 mg/l LD50 Rat 5800 mg/kg 0ral 2.2 ml/kg LD50 Rat 5800 mg/kg Butare (CAS 106-97-8) 2.2 ml/kg Acute 2.2 ml/kg Inhalation 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 1355 mg/l Disterior Rat 1355 mg/l LD50 Rate 1355 mg/l Disterior Rate 1355 mg/l Disterior Rate 1355 mg/l Dotation Rate 1355 mg/l LD50 Guinea pig 5900 mg/kg, Days Acute 14000000000000000000000000000000000000			> 9.4 ml/kg, 24 Hours
Oral 132 mg/l Doral 50.1 mg/l LD50 Rat Batance 5800 mg/kg 2.2 ml/kg Sutane (CAS 106-97-8) Acute Inhalation LC50 Mouse Rat Distribution Given pig Acute Dermal LD50 Guinea pig Abbit Abbit Mouse	Inhalation		
Oral 50.1 mg/l LD50 Rat 5800 mg/kg 2.2 ml/kg 2.2 ml/kg Butane (CAS 106-97-8) 2.2 ml/kg Acute 2.2 ml/kg Inhalation 2.2 ml/kg LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 1237 mg/l, 120 Minutes LC50 Mouse 1235 mg/l Diethylene Glycol Monoethyl Ether (-> t 11-90-0) 1355 mg/l Dermal E 2900 mg/kg, Days LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 24 Hours 714 mg/kg Oral E 714 mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg 600 mg/kg Mouse 6031 mg/kg 600 mg/kg LD50 Mouse 600 mg/kg Mouse 6031 mg/kg 600 mg/kg Abbit 600 mg/kg 600 mg/kg	LC50	Rat	55700 ppm, 3 Hours
Oral 5800 mg/kg LD50 Rat Solutane (CAS 106-97-8) 2.2 ml/kg Butane (CAS 106-97-8)			132 mg/l, 3 Hours
LD50 Rat 5800 mg/kg Jubic Jubic Jubic Acute Inhalation Jubic Inhalation Jubic S2 %, 120 Minutes LC50 Mouse 1357 mg/l, 120 Minutes Dermol Implementation S2 %, 120 Minutes Distribution S155 mg/l S100 mg/kg, 24 Mouse Distribution S100 mg/kg, 24 Mouse S100 mg/kg, 24 Mouse Distribution S100 mg/kg, 24 Mouse S100 mg/kg, 24 Mouse Oral Kabit S100 mg/kg, 24 Mouse S114 mg/kg Distribution Mouse Mouse Mouse S114 mg/kg Oral Kabit S000 mg/kg, 24 Mouse S114 mg/kg S114 mg/kg Distribution Kabit S000 mg/kg, 24 Mouse S114 mg/kg S114 mg/kg Distribution Kabit S000 mg/kg, 24 Mouse S11 mg/kg S114 mg/kg Distribution Kabit S000 mg/kg S114 mg/kg S114 mg/kg Mouse G01 mg/kg S11 mg/kg S114 mg/kg S114 mg/kg Mouse Kabit Kabit Kabit Kabit Kabit			50.1 mg/l
2.2 ml/kg Butane (CAS 106-97-8) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 500 mg/kg, 24 Hours 714 mg/kg Mouse Rabbit 500 mg/kg 500 mg/kg 600 mg/kg 500 mg/kg	Oral		
Autane (CAS 106-97-8) Acute Inhalation LC50 Mouse I237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l Diethylene Glycol Monoethyl Ether (CAS 111-90-0) Acute Derma/ LD50 Guinea pig Rabbit Guinea pig	LD50	Rat	5800 mg/kg
AcuteInhalationLC50Mouse1237 mg/l, 120 Minutes52 %, 120 Minutes52 %, 120 MinutesS2 %, 120 MinutesS2 %, 120 MinutesLD50RatGuinea pig5900 mg/kg, DaysLD50Guinea pigRabbit8500 mg/kg, 24 HoursArring MgOral1000000000000000000000000000000000000			2.2 ml/kg
Inhalation 1237 mg/l, 120 Minutes LC50 Mouse 52 %, 120 Minutes 52 %, 120 Minutes 1355 mg/l Diethylene Glycol Monoethyl Ether > 11-90-0) 1355 mg/l Acute 5900 mg/kg, Days Dermal 5900 mg/kg, Days LD50 Guinea pig 5900 mg/kg, 2 Hours Rabbit 8500 mg/kg, 24 Hours Varia 7714 mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Abuse 600 mg/kg	Butane (CAS 106-97-8)		
LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 52 %, 120 Minutes Fat 1355 mg/l Diethylene Glycol Monoethyl Ether (CAS 111-90-0) 1355 mg/l Acute 5900 mg/kg, Days Dermal 5900 mg/kg, Days LD50 Guinea pig Rabbit 8500 mg/kg, 2 Hours Arte 7714 mg/kg Dr 7714 mg/kg LD50 Guinea pig Mouse 6031 mg/kg Abute 600 mg/kg	Acute		
Rat 52 %, 120 Minutes Diethylene Glycol Monoethyl Ether (CAS 111-90-0) 1355 mg/l Acute Dermal Dermal 5900 mg/kg, Days LD50 Guinea pig 5900 mg/kg, 2 Hours Rabbit 8500 mg/kg, 24 Hours 0ral 7714 mg/kg LD50 Guinea pig 6031 mg/kg Arous 6031 mg/kg Rabbit 600 mg/kg	Inhalation		
Rat 1355 mg/l Distribution of the second	LC50	Mouse	1237 mg/l, 120 Minutes
Diethylene Glycol Monoethyl Ether (CAS 111-90-0) Acute Dermal LD50 Guinea pig 5900 mg/kg, Days Rabbit S500 mg/kg, 2 Hours 8476 mg/kg, 2 Hours 8476 mg/kg, 2 Hours 7714 mg/kg 7714 mg/kg Oral LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg 1 Mouse 600 mg/kg Rabbit 600 mg/kg			52 %, 120 Minutes
AcuteDermalLD50Guinea pig5900 mg/kg, DaysRabbit8500 mg/kg, 2 HoursKabbit8476 mg/kg, 24 HoursVariable7714 mg/kgD50Guinea pig4970 mg/kgMouse6031 mg/kgRabbit5600 mg/kgRabbit5600 mg/kg		Rat	1355 mg/l
DermalLD50Guinea pig5900 mg/kg, DaysRabbit8500 mg/kg, 2 HoursKabbit8476 mg/kg, 24 HoursToral714 mg/kgLD50Guinea pig4970 mg/kgMouse6031 mg/kgRabbit5600 mg/kgRabbit5600 mg/kg	Diethylene Glycol Monoeth	nyl Ether (CAS 111-90-0)	
LD50 Guinea pig 5900 mg/kg, Days Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 714 mg/kg Ora/ 714 mg/kg LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rabbit 5600 mg/kg	Acute		
Rabbit Rabbit 8500 mg/kg, 2 Hours 8476 mg/kg, 24 Hours 7714 mg/kg Oral LD50 Guinea pig 4970 mg/kg Mouse 6031 mg/kg Rabbit 5600 mg/kg Rat 5600 mg/kg			
OralDoralLD50Guinea pigMouse4970 mg/kgRabbit5600 mg/kgRat5600 mg/kg	LD50	Guinea pig	5900 mg/kg, Days
OralLD50Guinea pig4970 mg/kgMouse6031 mg/kgRabbit5600 mg/kgRat5600 mg/kg		Rabbit	8500 mg/kg, 2 Hours
OralLD50Guinea pig4970 mg/kgMouse6031 mg/kgRabbit5600 mg/kgRat5600 mg/kg			8476 mg/kg, 24 Hours
LD50Guinea pig4970 mg/kgMouse6031 mg/kgRabbit5600 mg/kgRat5600 mg/kg			7714 mg/kg
Mouse6031 mg/kgRabbit5600 mg/kgRat5600 mg/kg	Oral		
Rabbit5600 mg/kgRat5600 mg/kg	LD50	Guinea pig	4970 mg/kg
Rat 5600 mg/kg		Mouse	6031 mg/kg
		Rabbit	5600 mg/kg
		Rat	5600 mg/kg

Components	Species		Test Results
Propane (CAS 74-98-6)			
Acute			
Inhalation			
LC50	Mouse		1237 mg/l, 120 Minutes
			52 %, 120 Minutes
	Rat		1355 mg/l
			658 mg/l/4h
* Estimates for product may	be based on add	ditional component data not shown.	
Skin corrosion/irritation	Prolonged sk	in contact may cause temporary irrita	ation.
Serious eye damage/eye irritation	Causes serio	ous eye irritation.	
Respiratory or skin sensitization	on		
Respiratory sensitization	Not available		
Skin sensitization	This product	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity		No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
OSHA Specifically Regulat	ed Substances	(29 CFR 1910.1001-1050)	
Not listed.			
Reproductive toxicity	This product	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause d	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified	Not classified.	
Aspiration hazard	Not available	Not available.	
Chronic effects	Prolonged in	Prolonged inhalation may be harmful.	
12. Ecological informatio	n		
Ecotoxicity	Harmful to ac	quatic life.	
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours

(Oncorhynchus mykiss)
Diethylene Glycol Monoethyl Ether (CAS 111-90-0)

LC50

Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours
* Estimates for produ	ict may be based on	additional component data not shown	

Rainbow trout, donaldson trout

* Estimates for product may be based on additional component data not shown. **rsistence and degradability** No data is available on the degradability of this product.

Persistence and degradability N Bioaccumulative potential N

Fish

Bioaccumulative potential	No data available.	
Partition coefficient n-octan	ol / water (log Kow)	0.04
Acetone		-0.24
Butane		2.89
Diethylene Glycol Monoethyl E	Ether	-0.54
Propane		2.36
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmen	tal effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

4740 - 6330 mg/l, 96 hours

13. Disposal considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
US RCRA Hazardous Waste U List: Reference			
Acetone (CAS 67-64-1)	U002		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.		

14. Transport information

n	n.	т
יט	U	Ι.

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
	Passenger and cargo aircraft	Allowed.
	Cargo aircraft only	Allowed.
	Packaging Exceptions	LTD QTY
IME	DG	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	
	Marine pollutant	No.
	EmS	F-D, S-U

Product name: Lemon Metered Air Freshener

Special precautions for user
Packaging ExceptionsRead safety instructions, SDS and emergency procedures before handling.
LTD QTYTransport in bulk according to
Annex II of MARPOL 73/78 and
the IBC CodeNot applicable.

DOT



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) **Hazard categories** Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA) Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number** Acetone (CAS 67-64-1) 6532 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c)) Acetone (CAS 67-64-1) 35 %WV **DEA Exempt Chemical Mixtures Code Number** Acetone (CAS 67-64-1) 6532 US state regulations **US. Massachusetts RTK - Substance List** Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6) US. New Jersey Worker and Community Right-to-Know Act Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6) US. Pennsylvania Worker and Community Right-to-Know Law Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6) **US. Rhode Island RTK**

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-06-2014	
Revision date	08-03-2015	
Version #	03	
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.	

Transport information: General information GHS: Classification