

1. Identification

Product identifier ARSENAL STRIPPER

Other means of identification

SDS number 538N-14A

Product code HIL00826

Recommended use Stripper

Recommended restrictions For Labeled Use Only

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.
St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (800) 365-1555 (Ext. 8206)

Fax (816) 383-8406

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Acute toxicity, dermal Category 4

Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 4

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. Harmful if inhaled. May cause respiratory irritation. Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. In case of fire: Use appropriate media to extinguish. If swallowed: Do not induce vomiting. Drink large quantities of water. Call a physician immediately.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law. Waste from normal use may be sewered to a public-owned treatment works in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butoxyethanol		111-76-2	50 - < 60
Benzyl Alcohol		100-51-6	20 - < 30
Ethanolamine		141-43-5	10 - < 20
Other components below reportable levels			3 - < 5

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth thoroughly. Drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m ³
		50 ppm
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m ³
		3 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Ethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m ³
		5 ppm
Ethanolamine (CAS 141-43-5)	STEL	15 mg/m ³
		6 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
	TWA	8 mg/m3
		3 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m3
		10 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Chemical safety goggles when working with concentrate.

Skin protection

Hand protection Chemical resistant gloves.

Other Do not get this material in contact with skin.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards None known.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear, colorless liquid
Physical state	Liquid.
Form	Liquid.
Color	Clear colorless or nearly colorless
Odor	Solvent odor
Odor threshold	Not available
pH	11 - 12
Melting point/freezing point	Not applicable / Not available

Initial boiling point and boiling range	250 °F (121.11 °C)
Flash point	162.0 °F (72.2 °C) Tag Closed Cup
Evaporation rate	< 1 (ethyl ether = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.49 mm Hg
Vapor density	3.6 Air=1
Relative density	0.96 at 77°F
Solubility(ies)	
Solubility (water)	Appreciable
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	8.05 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	> 98 %
VOC	98.65 % US EPA VOC 68.65 CARB VOC

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes severe skin burns. Harmful in contact with skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics	Headache. Nausea, vomiting. Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
---	---

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin.

Components	Species	Test Results
Benzyl Alcohol (CAS 100-51-6)		
Acute		
Dermal		
LD50	Rabbit	2000 mg/kg
Inhalation		
LC50	Rat	1000 mg/l, 8 Hours
Oral		
LD50	Rat	1230 - 3100 mg/kg
Butoxyethanol (CAS 111-76-2)		
Acute		
Oral		
LD50	Rat	560 mg/kg
Ethanolamine (CAS 141-43-5)		
Acute		
Dermal		
LD50	Rabbit	1025 mg/kg
Oral		
LD50	Rat	10.2 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

Product	Species		Test Results
ARSENAL STRIPPER			
Aquatic			
Crustacea	EC50	Daphnia	190.189, 48 hours
Fish	LC50	Fish	182.0241, 96 hours
<i>Acute</i>			
Crustacea	EC50	Daphnia	81.5101, 48 hours estimated
Fish	LC50	Fish	28.307, 96 hours estimated
Components	Species		Test Results

Benzyl Alcohol (CAS 100-51-6)

Aquatic

Acute

Fish LC50 Bluegill (*Lepomis macrochirus*) 10, 96 hours

Butoxyethanol (CAS 111-76-2)

Aquatic

Acute

Fish LC50 Inland silverside (*Menidia beryllina*) 1250, 96 hours

Ethanolamine (CAS 141-43-5)

Aquatic

Acute

Fish LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss) >= 114 - <= 196 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl Alcohol	1.1
Butoxyethanol	0.83
Ethanolamine	-1.31

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Waste from normal product use may be sewer to a public owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

UN number	NA1760
UN proper shipping name	Compounds, Cleaning Liquid, (Monoethanolamine)
Transport hazard class(es)	
Class	8

Subsidiary risk	-
Label(s)	8
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B2, IB2, N37, T11
Packaging exceptions	154
Packaging non bulk	202
Packaging bulk	242
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.
DOT	



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butoxyethanol (CAS 111-76-2)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-20-2014

Revision date 08-14-2023

Version # 04

HMIS® ratings
Health: 3
Flammability: 2
Physical hazard: 0

Disclaimer
No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.

Revision information
Physical & Chemical Properties: Multiple Properties
Toxicological Information: Toxicological Data